

475 Series Automatic Cutting Machine



Voltage Options: 120 / 208 / 230 / 400 / 480 / 600 Volts
(power requirements vary with machine configuration)
Single or Three Phase, 100 psi Air
Dimensions: 36" long x 34" wide x 36" tall
Weight: 300 pounds

Applicable Materials:


**NON-WIRE
RUBBER HOSE
& TUBING**



HOSE GUARD



STEEL CABLE



PTFE HOSE



475 A

(Air Guillotine)

Application	Size
Non-Wire Hose	1 1/4"

Air Guillotine (A):

Marken's Air Guillotine cut method works for non-wire hose and small battery cable, allowing for a clean, square cut, with no contamination.

475 S

(Saw)

Application	Size
Hose Guard	6" Flat

Saw (S):

The 475S is a special design for cutting hose sleeve. With a special blade and clamping system to not only measure and cut sleeve but to also "sear" the end without sealing it closed. This provides a nice clean end with very little fraying and no need to further handle the sleeve prior to assembly.

Accessories:



Coilers Page 11



Dispersing Racks Page 10



Reelers Page 10



Platters Page 10



Collection Bin



Payouts Page 9

Options:


Depth Marking, InkJet Lay Line, Part Number, Logo and or Bar Code Marking



PC Control/Kit Cutting Technology



Splice Detection



- Rate of feed up to 100 FPM for 475S
160 FPM for 475A
- Up to 2000 cuts per hour
- Accuracy .1 to .3 percent of length (exceeds SAE standards)
- CPK of 1.67 or greater