

500 Series Automatic Cutting Machine



Voltage Options: 208 / 230 / 400 / 480 / 600 Volts
Three Phase, 100 psi Air
Dimensions: 34" long x 34" wide x 56" tall
Weight: 1,000 pounds

Applicable Materials:


NON-WIRE
RUBBER HOSE
& TUBING



HYDRAULIC
HOSE



STEEL CABLE



PTFE HOSE



COVERED
CABLE



500 A

(Air Guillotine)

Application	Size	
Non-Wire Hose	less than 3" OD	Air Guillotine (A): Marken's Air Guillotine cut method works for non-wire hose and small battery cable, allowing for a clean, square cut, with no contamination.

500 S

(Saw)

Application	Size	
Non-Wire Hose	1 1/4"	Saw (S): Marken Mfg. has set the world-wide standard for cutting hydraulic hose with the application of our wet cut system, coupled with our specially designed blade.
Hydraulic Hose	3/4" two wire 1" one wire	
PTFE Hose	1" flared end	

Accessories:



Coilers Page 11



Dispensing Racks Page 10



Reelers Page 10



Platters Page 10



Collection Bin



Payouts Page 9

Options:

Depth Marking, InkJet Lay Line, Part Number, Logo and or Bar Code Marking



PC Control/Kit Cutting Technology



Splice Detection



Guillotine - 500S only



- Rate of feed up to 150 FPM
- Up to 750 cuts per hour
- Accuracy .1 to .3 percent of length (exceeds SAE standards)
- CPK of 1.67 or greater